



		Declaration of Performance - Ref.No 2370 acc. to REGULATION (EU) No 305/2011 Article 4
1.	Identification code of product-type	P2 ClassicBoard P2 F**** - 2370
2.	Intended use	Boards for interior fitments (including furniture) for use in dry conditions.
3.	Manufacturer	Pfleiderer Deutschland GmbH, Ingolstädter Str. 51, D-92318 Neumarkt
4.	Authorised representative	not relevant
5.	System of assessment and verification	System 4
6.	Assessment of performance	not relevant
7.	European Technical Assessment	not relevant



	Thickness	≤ 8.9 mm	> 8.9 mm to ≤ 13 mm	> 13 mm to ≤ 20 mm	> 20 mm to ≤ 25 mm	> 25 mm to ≤ 32 mm	> 32 mm to ≤ 40 mm	> 40 mm	Harmonised
Essential characteristics/main features	Unit	Declared performance						specification	
Reaction to fire		E D-s2,d0 according to EN 13986 dependent on end use (Thickness: ≥9 mm / Gross density: ≥600 kg/m³)						iess: ≥9	EN 13986:2004 +A1:2015
Water vapour permeability, wet cup µ		15							-
Water vapour permeability, dry cup µ		50							
Class, formaldehyde release		F****							
Release (Content), pentachlorophenol (PCP)	< 3	3							
Airborne sound insulation (surface mass)		NPD							
Sound Absorption frequency range 250 Hz to 500 Hz		0.1							
Sound Absorption frequency range 1000 Hz to 2000 Hz		0.25							
Thermal conductivity (density)	W/(mK)	0.12							1
Air permeability NPD									1
Internal bond	N/mm ²	0.4	0.4	0.35	0.3	0.25	0.2	0.2	
Swelling in thickness, 24 h		NPD							
Internal bond after boil test	NPD						1		

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

Date of issue: 2020-04-07

i. V. Claus Seemann Head of productmanagement core materials (Document was created electronically and is therefore valid without signature!)

NPD: performance not defined